

Technical Data Sheet

BIVOS Oil Wax No. 375

For refreshing and finishing oiled surfaces.



Range of application	For interior timber after pre-treatment with LIVOS products. For maintaining of previously waxed or oiled timber; for restoration of old furniture or wood carvings. For the care of KERA Cott and linoleum.
Technical qualities	Transparent, velvet gloss, moisture resistant, antistatic finish. DIN EN 71 Part 3 certified.
Declaration of contents	Linseed oil, linseed oil - stand oil natural resin ester, linseed oil – stand oil, orange oil, isoaliphate, beeswax, micronized wax, carnauba wax, pine oil, alumina, rosemary oil and lead-free drying agents.
Colours	Clear. Tinting possible through a maximum 10 % addition of VINDO Natural Oil Paint No. 629.
Dilution	Delivered ready to use.
Application method	Brush, spray device, roller or wadded cloth application.
Coverage	1 liter (1,06 fl. quart.) is sufficient in wadded by cloth application and for pre-treated surfaces for approximately 100 m ² (1076 ft ²), for other modes of application for approximately 20 - 40 m ² (215 - 430 ft ²). Coverage could be considerably less depending upon the condition and absorbency of the surface. Always do a test application!
Cleaning up	Clean equipment immediately after use with SVALOS Thinner No. 222.
Drying time	At 23°C and 50% relative humidity and application by wadded cloth approximately 20 – 30 minutes. Application by brush, spray device or roller drying time requires 30 – 120 minutes, depending on thickness of application up to 24 hrs.
Specific gravity	0.84 g/ ml.
Safety advice	<p>Always be sure to store cleaning cloth, sponges, etc. that are still wet or even slightly moist with BIVOS-Oil-Wax No. 375 in an airtight metal container or in water, as there is a danger of spontaneous combustion caused by the linseed oil in the product.</p> <p>The product alone will not undergo spontaneous combustion.</p> <p>S 2 Keep out of reach of children</p> <p>S 62 If swallowed, do not induce vomiting. Seek medical assistance immediately, and bring along the container or this leaflet.</p>
Disposal	According to locally regulated laws.
Container sizes	0.05 l; 0,125 l; 0.25 l; 0.75 l; 2.5 l; 10 l; 30 l; 200 l.
Storage	Cool and dry, please see label for expiration date.

See reverse for Application Instructions

June 2003 Rev. 1.2



Plantchemistry with the longest experience worldwide

Manufactured by LIVOS Pflanzenchemie GmbH + Co. KG, D-29568 Wieren, Germany

How to use

BIVOS Oil Wax No. 375

For refreshing and finishing oiled surfaces.

Preparation

The surface must be dry, solid, clean, and free of grease and dust. Pretreat timber with LIVOS oils or stains like MELDOS Natural Resin Hardening Oil No. 264, ARDVOS Wood Oil No. 266, GORMOS Wax Oil No. 267 or DARIX Transparent Wood Stain No. 297

Application

Stir or shake product thoroughly before using. Apply very thinly; it is best to use a cloth to rub the product in vigorously. Polishing of the surface after treatment is not necessary. With other application methods (brush, roller, or spray), careful attention must be paid to applying a very thin and even coat. Excess product should be removed with a cloth. After 20 - 30 minutes of drying time, polish surface with a brush or a clean cloth. 1 - 2 hours after polishing, surface will be dry to the touch.

Industrial application: via spray and brush techniques (please request technical advice if necessary).

Renovation

According to the application, treat surface with LIVOS products, then apply BIVOS Oil Wax No. 375. Always test for compatibility with existing surface coatings before use.

LIVOS products contain organically sourced ingredients and are never tested on animals.

These directions are the result of long years of research and practical testing. They are backed by our most current expert information. New findings may invalidate this information. This data sheet is meant to serve as information and instruction. No legal liability should be interpreted from it. In case of doubt, please contact the retailer, wholesaler, or manufacturer.



Plantchemistry with the longest experience worldwide

Manufactured by LIVOS Pflanzenchemie GmbH + Co. KG, D-29568 Wieren, Germany